

# **OP801G GPON ONU**

## **Specifications**

**OPTICO COMMUNICATION**

---

<b>Version</b>	<b>Date</b>	<b>Author</b>	<b>Reviewers</b>	<b>Remark</b>
V1.0	2017/2/18			Shall not disclose to any third party

© 2018 OPTICO. All rights reserved.

Copyright Notice:

This document is copyright owned by Optico Communication. It refers to proprietary information of Shenzhen Optico Communication Co.,Ltd, any entity unit or individual cannot use and leak any images, tables, data, and other information which contains without written permission by Shenzhen Optico Communication Co.,Ltd.

The information in this document will be updated continually with the progress of Shenzhen Optico Communication Co., Ltd.

# Contents

<b>1.Overview .....</b>	<b>4</b>
1.1 Product Positioning .....	4
1.2 Network Mode.....	4
<b>2.Hardware Feature .....</b>	<b>4</b>
2.1 Interface of device.....	4
2.2 Indicators of device .....	5
<b>3.Technical specifications .....</b>	<b>6</b>
3.1 Physical structure, Environment and Electrical parameter.....	6
3.2 GPON Interface Specifications.....	6
3.3 Special function .....	6

# 1.OVERVIEW

---


## 1.1 Product Positioning

OP801G terminal devices are designed for fulfilling FTTH and triple play service demand of fixed network operators or cable operators. The box is based on the mature Gigabit GPON technology, which have high ratio of performance to price. They are highly reliable and easy management and guaranteed QoS. And It is fully compliant with technical regulations such as ITU-T G.984.x.

## 1.2 Network Mode

OP801G is the FTTH mode terminal equipment which designed for indoor applications.

Specific application refers to Picture 1-1



Picture 1-1 OP801Gproducts Network diagram

# 2.HARDWARE FEATURE

---

## 2.1 Interface of device

OP801G product figure as Picture 2-1



Picture 2-1 OP801G product figure

Table 2-1 Description OP801GequipmentInterface

Port Type	Function
PON port	Connect PON port with internet by SC type, single mode optical fiber cable
LAN port	RJ45Port connects to local internet, 1 GE port automatically
Reset button (RST)	Press down reset button and keep 1-5 seconds to make the device restart and recover from the factory default Settings.
PWR port (DC12 V)	Connect with power adapter
Power turn on/off	Power turn on/off

## 2.2 Indicators of device

Table 2-2 OP801G LED statement

Indicators	status	Description
POWER	Light on	ONU power supply normally
	Light off	ONU no power supply
PON	Light on	ONU link active
	Flash	ONU manage to link
	Light off	ONU receiving power rate lower than optical receiver sensitivity
LOS	Blink	Device does not receive optical signals.
	off	Device has received optical signal.
LAN	Light on	network port linked, but no data transmitting
	Flash	network port data pass
	Light off	ONU no power supply or internet cable unlink

## 3. TECHNICAL SPECIFICATIONS

### 3.1 Physical structure, Environment and Electrical parameter

Table 3-1 OP801G specification and working environment

Parameter	Nominal
Dimension	107mm×85mm×26mm (L×W×H)
Net weight	0.26kg
Typical power consumption	<7W
Noise	None
Cooling style	Naturally cooling
Power supply	12V DC (By external AC/DC adapter)
Installation style	Support PC, wall mount or put inside of information box.
Environment	0~45℃
Atmospheric pressure	70~106Kpa
MTBF	50,000hours
MTTR	30minutes
Parameter	Nominal

### 3.2 GPON Interface Specifications

Table 3-2 OP801G GPON Interface

Parameter	Nominal
Connector style	SC/PC
PON quantity	1
Fiber style	Single mode
Wavelength	TX: 1310 +/-20nm RX: 1490 +/-10nm
PON interface standard	ITU-T G.984.2/ITU-T G.984.3/ITU-TG.988 Class B+
PON interface receiving rate	1.244Gpbs
PON interface transmitting rate	2.488Gpbs
Output optical power	Min: 0dBm                      Max: +5dBm
Opticalreceiver sensitivity	Precede -28dBm
The length of the optical R	Max 20km

### 3.3 Software function

Mode: HGU

## ***OPTICO COMMUNICATION***

---

- Support TR069,NAT,DMZ,DNS features
- Support IGMP multicast and using bandwidth efficiently.
- Support Multiple VLAN
- Support network storm control.
- Support IPV6 ,PPPoE, DHCP and Static IP configuration for WAN Interface
- Support IP, MAC filtering, Firewall Functionality in routed mode

Mode: SFU

- Support Multiple VLAN
- Support network storm control.
- Support IP, MAC filtering, Firewall Functionality in routed mode